

# GLOBAL STONE

## NATURAL STONE PAVING

### DECLARATION OF PERFORMANCE

**Date : 19 Dec 2019**

**No: Ceramic/01/2019**

1. Unique identification of the product type: **Ceramic Tile**
2. Type No. **Vitrified Tiles.**
3. Intended use of the construction product, in accordance with EN ISO 10545:1997, 10545:2012 and 10545:2015  
**Outdoor Paving.**
4. Name and address of the manufacturer: **SHREE AGENCIES PVT. LTD., 233, Shopping Centre, Kota (Rajasthan) India**
5. System of assessment and verification of constancy of performance: **System 4.**
6. Harmonized standard reference: **EN ISO 10545:1997, 10545:2012 and 10545:2015.**  
**(a) Initial type testing as per UNE-EN ISO 10545-3:1997, 10545-12:1997, 10545-6:2012, 10545-4:2015 and DIN 51130:2014.**  
**(b) Factory Production Control as per EN ISO 10545:1997, 10545:2012 and 10545:2015.**
7. Declared Performances:

Essential Characteristics	Performance Value	Relevant Clause
<b>Freez/Thaw resistance</b> Before and after 100 cycles	No defects	10545-12:1997
<b>Freez/Thaw resistance</b> (De-icing Salts)	NPD (No National Annex to std)	
<b>Slip resistance</b> <b>(Wet value)</b>	21.5 <sup>0</sup>	DIN 51130:2014-02 and ISO 10545- 17:2017 Method "C"
<b>Water Absorption</b> (Mean Value)	0.01%	10545-3:1997
<b>Deep Abrasion Resistance</b> (Mean Value)	119	10545-6:2012
<b>Release of dangerous Substances</b>	NPD (No National Annex to std)	
<b>Bending Resistance</b>	40,0 (N/mm <sup>2</sup> )	10545-4:2015
<b>Critical Angle of slip</b>	22,8 <sup>0</sup>	DIN 51130:2014 Apdo.5(*) (1)

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mr. Ravi Goyal  
Manager