



VITRIPIAZZA®

Vitrified Porcelain Paving

Declaration of Performance

Vitripiazza Bellstone

No. Bellstone2021V1

1. Unique identification code of the product type:

Dry-pressed porcelain tiles, with water absorption Eb ≤ 0,5%

2. Intended use:

For internal and external floorings and walls

3. Name or registered trade mark, and contact address of the manufacturer:

Decros Yapi San Tic. A.Ş. Kordon V.D – 2710831776 Alsancak – Konak - İZMİR

4. System of assessment and verification of constancy of performance (AVCP):

System 4

5. Name and identification number of notified laboratory, if relevant:

Not Relevant

6. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	A1FL/A1	EN 14411:2012
Release of dangerous substances. for:		
Cadmium:	> 0.07 mg/dm ²	
Lead:	> 0.08 mg/dm ²	
Breaking strength:	> 1300N	
Slipperiness:	See table below	
Tactility	NPD	
Bond/Strength adhesion, for:		
Cementitious adhesive, type C2:	NPD	
Thermal shock resistance:	Pass	
Durability for:		
Internal use:	Pass	
External use (freeze/thaw resistance)	Pass	

RANGE	DIN51130	DIN51097	UNE-ENV 12633:2006	BCRA	BS 7976:2002	
					Dry	Wet
Bellstone	R11	A+B+C	N/A	N/A	PTV > 36	PTV > 36

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer declared in point 3.

Signed for and on behalf of the manufacturer by: Savas Basar Okcu Assistant Factory Manager

Place and date of issue: Izmir Turkey

April 2018

Signature:

Savas Basar Okcu

 M.C.M. İnşaat ve Sanayi Tic. Ltd. Şti.
 Seramik İnş. ve İnş. Mlz. San. ve Tic. Ltd. Şti.
 K. No: 50, Kemalpaşa/İZMİR/ Türkiye
 No: 303/3 Kemalpaşa/İZMİR, K. No: 509 016 7816
 Tic. Sic. Mhk. 116215/Sb1: 169512 Sb2: 190040
 Mersis No: 0809 0157 8100 0014