



VITRIPIAZZA®

Vitrified Porcelain Paving

Declaration of Performance

Vitripiazza Nerali

No. Nerali2021V1

1. Unique identification code of the product type:

Dry-pressed porcelain tiles, with water absorption $E_b \leq 0,5\%$

2. Intended use:

For internal and external floorings and walls

3. Name or registered trade mark, and contact address of the manufacturer:

Keradom SRL - Via Val Rossenna 113/115 - 41040 - Polinago - MO ITALY

4. System of assessment and verification of constancy of performance (AVCP):

System 3 and 4

5. Name and identification number of notified laboratory, if relevant:

Modena Centro Prove s.r.l. - Via Sallustio no 78 Modena (MO) Italy. Identification number 1599

6. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	A1 _{FL} /A1	EN 14411:2012
Release of dangerous substances. for:		
Cadmium:	NPD	
Lead:	NPD	
Breaking strength: (Thickness > 7.5mm)	$\geq 700N$	
Slipperiness:	See table below	
Tactility	NPD	
Bond/Strength adhesion, for:		
Cementitious adhesive, type C2:	$\geq 0.5 Nmm^2$	
Thermal shock resistance:	Pass	
Durability for:		
Internal use:	Pass	
External use (freeze/thaw resistance)	Pass	

RANGE	DIN51130	DIN51097	UNE-ENV 12633:2006	BCRA	BS 7976:2002	
					N/A	N/A
Nerali	R10	N/A	N/A	N/A		

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer declared in point 3.

Signed for and on behalf of the manufacturer by: Giovanni Rinaldi Amm.re Unico

Place and date of issue: Rubiera (RE)

9/06/15

Signature:

Keradom srl

Signature