



VITRIPIAZZA®

Vitrified Porcelain Paving

Declaration of Performance

Vitripiazza Mattoni

No. Mattoni2021V1

1. Unique identification code of the product type:

Dry-pressed porcelain tiles, with water absorption $E_b \leq 0,5\%$

2. Intended use:

For internal and external floorings and walls

3. Name or registered trade mark, and contact address of the manufacturer:

Ceramiche Atlas Concorde Spa, Via Canaletto 141 – 41042 Spezzano di Fiorano (MO) – ITALY

4. System of assessment and verification of constancy of performance (AVCP):

System 4

5. Name and identification number of notified laboratory, if relevant:

Not Relevant

6. Declared performances:

| Essential characteristics | Performance | Harmonized technical specification |
|---------------------------------------|-----------------|------------------------------------|
| Reaction to fire: | A1FL/A1 | EN 14411 |
| Release of dangerous substances, for: | | |
| Cadmium: | NPD | |
| Lead: | NPD | |
| Breaking strength: | > 1300N | |
| Slipperiness: | See table below | |
| Tactility | NPD | |
| Bond/Strength adhesion, for: | | |
| Cementitious adhesive, type C2: | NPD | |
| Thermal shock resistance: | Pass | |
| Durability for: | | |
| Internal use: | Pass | |
| External use (freeze/thaw resistance) | Pass | |

| RANGE | DIN51130 | DIN51097 | UNE-ENV 12633:2006 | BCRA | BS 7976:2002 | |
|---------|----------|----------|--------------------|-------|--------------|----------|
| | | | | | Dry | Wet |
| Mattoni | R11 | A+B+C | class 3 (Rd > 45) | >0,40 | PTV > 36 | PTV > 36 |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer declared in point 3.

Signed for and on behalf of the manufacturer by: Maurizio Mazzotti (Amministratore Delegato – Managing Director)

Place and date of issue: Spezzano di Fiorano (MO) – ITALY

Signature:

11/12/2019