



VITRIPIAZZA®

Vitrified Porcelain Paving

Declaration of Performance

Vitripiazza Norde

No. Norde2021V1

1. Unique identification code of the product type:

Dry-pressed porcelain tiles, with water absorption Eb ≤ 0,5%

2. Intended use:

For internal and external floorings and walls

3. Name or registered trade mark, and contact address of the manufacturer:

Ceramiche Atlas Concorde Spa, Via Canaletto 141 – 41042 Spezzano di Fiorano (MO) – ITALY

4. System of assessment and verification of constancy of performance (AVCP):

System 4

5. Name and identification number of notified laboratory, if relevant:

Not Relevant

6. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	A1 _{FL} /A1	EN 14411
Release of dangerous substances. for:		
Cadmium:	NPD	
Lead:	NPD	
Breaking strength:	> 1300N	
Slipperiness:	See table below	
Tactility	NPD	
Bond/Strength adhesion, for:		
Cementitious adhesive, type C2:	NPD	
Thermal shock resistance:	Pass	
Durability for:		
Internal use:	Pass	
External use (freeze/thaw resistance)	Pass	

RANGE	DIN51130	DIN51097	UNE-ENV 12633:2006	BCRA	BS 7976:2002	
					Dry	Wet
Norde	R11	A+B+C	class 3 (Rd > 45)	>0,40	PTV > 36	PTV > 36

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer declared in point 3.

Signed for and on behalf of the manufacturer by: Maurizio Mazzotti (Amministratore Delegato – Managing Director)

Place and date of issue: Spezzano di Fiorano (MO) – ITALY

Signature:

30/04/21