

SAFETY DATA SHEET CODE LUXGPA DATE 12.16

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### **1.1 Product identifier**

Product name: Use: Supplier: Luxigraze Adhesive Adhesive Natural Paving Products (UK) Ltd Belton Road Sandtoft Doncaster North Lincolnshire DN8 5SX Tel: 0330 333 8030 Fax: 0330 333 8040 Email: enquiries@luxigraze.co.uk

### **SECTION 2 HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

Classification under CLP:	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20; -: R52/53	
Classification under CHIP:	Carc. 2: H351; STOT RE 2: H373; Acute Tox. 4: H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335; Skin Sens. 1: H317; Resp. Sens. 1: H334	
Most important adverse effects:	Harmful by inhalation. Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact.	
Harmful:	danger of serious damage to health by prolonged exposure through inhalation. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
2.2. Label elements		
Label elements under CLP:		
Hazard statements:	H315: Causes skin irritation.	
	H317: May cause an allergic skin reaction.	
	H319: Causes serious eye irritation.	
	H332: Harmful if inhaled.	
	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
	H335: May cause respiratory irritation.	
	H351: Suspected of causing cancer.	
	H373: May cause damage to organs . through prolonged or repeated exposure through prolonged or repeated inhalative exposure.	
Signal words:	Danger	
Hazard pictograms:	GHS07: Exclamation mark GHS08: Health hazard	



### SAFETY DATA SHEET CODE LUXGPA DATE 12.16

Precautionary statements:	P280: Wear protective gloves/protective clothing/eye protection/ face protection.
	P285: In case of inadequate ventilation wear respiratory protection.
	P302+352: IF ON SKIN: Wash with plenty of soap and water.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	P403+233: Store in a well-ventilated place. Keep container tightly closed.
	P501: Dispose of contents/container to to hazardous or special waste waste collection point.
Label elements under CHIP:	
Hazard symbols:	Harmful.
	*
Risk phrases:	R20: Harmful by inhalation.
	R36/37/38: Irritating to eyes, respiratory system and skin.
	R40: Limited evidence of a carcinogenic effect.
	R42/43: May cause sensitisation by inhalation and skin contact.
	R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases:	S23: Do not breathe vapour.
	S38: In case of insufficient ventilation, wear suitable respiratory equipment.
	S36/37: Wear suitable protective clothing and gloves.
	S24/25: Avoid contact with skin and eyes.
	S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
	S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.
Precautionary phrases:	Contains isocyanates. See information supplied by the manufacturer.
2.3. Other hazards	
PBT:	This substance is not identified as a PBT substance.



SAFETY DATA SHEET CODE LUXGPA DATE 12.16

### SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Hazardous ingredients:	DIPHENYLMETHANE-4,4'-DI-ISOCYANATE
	EINECS 202-966-0
	CAS 101-68-8
	CHIP Classification Xn: R40; Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43
	CLP Classification - Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335
	Percent 30-60%
	TRIPHENYL PHOSPHITE
	EINECS 202-908-4
	CAS 101-02-0
	CHIP Classification Xi: R36/38; N: R50/53
	CLP Classification - Eye Irrit. 2: H319; Skin Irrit. 2: H315; Aquatic Chronic 1: H410;
	Aquatic Acute 1: H400
	Percent 1-5%

### **SECTION 4 FIRST AID MEASURES**

4.1. Description of first aid measures		
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.	
	Wash immediately with plenty of soap and water.	
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.	
Ingestion:	Wash out mouth with water. Consult a doctor.	
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so.	
4.2. Most important symptoms and effects, both acute and delayed		
Skin contact:	There may be irritation and redness at the site of contact. Onset of symptoms may be delayed.	
Eye contact:	There may be irritation and redness. The eyes may water profusely.	
Ingestion:	There may be soreness and redness of the mouth and throat.	
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Onset of symptoms may be delayed.	
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.	
4.3. Indication of any immediate medical attention and special treatment needed		
Immediate / special treatment:	Eye bathing equipment should be available on the premises.	



### SAFETY DATA SHEET CODE LUXGPA DATE 12.16

### SECTION 5 FIRE FIGHTING MEASURES

5.1. Extinguishing media		
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.	
5.2. Special hazards arising from the substance or mixture		
Exposure hazards:	In combustion emits toxic fumes	
5.3. Advice for fire-fighters		
Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.	

### SECTION 6 ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.	
6.2. Environmental precautions		
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.	
6.3. Methods and material for containment and cleaning up		
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.	
6.4. Reference to other sections		
Reference to other sections:	Refer to section 8 of SDS.	

#### **SECTION 7 HANDLING AND STORAGE**

7.1. Precautions for safe handling	
Handling requirements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.
7.2. Conditions for safe storage, including	any incompatibilities
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed.
Suitable packaging:	Must only be kept in original packaging.
7.3. Specific end use(s)	
Specific end use(s):	adhesive



SAFETY DATA SHEET CODE LUXGPA DATE 12.16

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters	
Workplace exposure limits:	8 hour TWA 0.02mg/m3
	15 min. STEL 0.07mg/m3
Hazardous ingredients:	DIPHENYLMETHANE-4,4'-DI-ISOCYANATE
Workplace exposure limits:	8 hour TWA 0.02mg/m3
	15 min. STEL 0.07mg/m3
8.2. Exposure controls	
Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.
Hand protection:	Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves, the user must COSHH risk assess to determine the correct glove.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

State:	Liquid
Colour:	Green
Odour:	Characteristic odour
Evaporation rate:	Slow
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Reacts with water.
Viscosity:	Viscous
Flash point°C:	>93
Autoflammability°C:	>600
Vapour pressure:	0.01Pa
Relative density:	1.23
9.2. Other information	Not applicable



### SAFETY DATA SHEET CODE LUXGPA DATE 12.16

### SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity	
Reactivity:	Stable under recommended transport or storage conditions.
10.2. Chemical stability	
Chemical stability:	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
Hazardous reactions:	Hazardous reactions will not occur under normal transport or storage conditions.
	Decomposition may occur on exposure to conditions or materials listed below.
10.4. Conditions to avoid	
Conditions to avoid:	Heat.
10.5. Incompatible materials	
Materials to avoid:	Strong oxidising agents. Strong acids.
10.6. Hazardous decomposition products	
Haz. decomp. products:	In combustion emits toxic fumes.

### SECTION 11 TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

### **Toxicity values:**

ROUTE	SPECIES	TEST	VALUE	UNITS
ORAL	RAT	LD50	>10000	mg/kg
DERMAL	RBT	LD50	>9400	mg/kg

#### **Relevant effects for mixture:**

EFFECT	ROUTE	BASIS
Acute toxicity (harmful)	INH	Hazardeous: calculated
Irritation	OPT INH DRM	Hazardeous: calculated
Sensitisation	INH DRM	Hazardeous: calculated
Repeated dose toxicity	INH	Hazardeous: calculated

### Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact. Onset of symptoms may be delayed
Eye contact:	There may be irritation and redness. The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Onset of symptoms may be delayed.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.



### SAFETY DATA SHEET CODE LUXGPA DATE 12.16

### **SECTION 12 ECOLOGICAL INFORMATION**

. .

. . . . . .

#### 12.1. Toxicity

.....

. . .

**Ecotoxicity values:** 

SPECIES	TEST	VALUE	UNITS
Aquatic plants	72H EC50	1640	mg/l
Daphnia magna	24H EC50	>1000	mg/l
Sludge	3H EC50	>100	mg/l
Zebrafish (Brachydanio rerio)	96H LC50	>1000	mg/l

12.2. Persistence and degradability	
Persistence and degradability:	Biodegradable in part only.
12.3. Bioaccumulative potential	
Bioaccumulative potential:	No data available.
12.4. Mobility in soil	
Mobility:	Readily absorbed into soil.
12.5. Results of PBT and vPvB assessmen	t
PBT identification:	This substance is not identified as a PBT substance.
12.6. Other adverse effects	
SECTION 13 WASTE DISPOSAL	
13.1. Waste treatment methods	
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal company.
	Disposal of packaging: Arrange for disposal by a licenced waste disposal company
	NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.
SECTION 14 TRANSPORT INFORMATION	
Transport class:	This product does not require a classification for transport.
SECTION 15 REGULATORY INFORMATION	1
15.1. Safety, health and environmental reg	ulations/legislation specific for the substance or mixture
Specific regulations:	This product is classifed as a mixture. CLP classification for information only. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product

# according to standard EN 14387) is used.15.2. Chemical Safety Assessment:A chemical safety assessment has not been carried out for the<br/>substance or the mixture by the supplier.

should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1



# SAFETY DATA SHEET

CODE LUXGPA DATE 12.16

### **SECTION 16 OTHER INFORMATION**

### Other information

Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010, using the current safety information supplied by the distributors of the component materials. This leaflet may contain inappropriate information under particular conditions of use.	
Phrases used in s.2 and 3:	H315: Causes skin irritation.	
	H317: May cause an allergic skin reaction.	
	H319: Causes serious eye irritation.	
	H332: Harmful if inhaled.	
	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
	H335: May cause respiratory irritation.	
	H351: Suspected of causing cancer <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state>	
	H373: May cause damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through prolonged or repeated exposure <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state></or>	
	H410: Very toxic to aquatic life with long lasting effects.	
	R20: Harmful by inhalation.	
	R36/37/38: Irritating to eyes, respiratory system and skin.	
	R36/38: Irritating to eyes and skin.	
	R40: Limited evidence of a carcinogenic effect.	
	R42/43: May cause sensitisation by inhalation and skin contact.	
	R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.	
	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment	
Legal disclaimer:	This product is for professional use only and should be used as directed. For further information consult the application data sheet. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The company shall not be held liable for any damage resulting from handling or from contact with the above product.	