

**DECLARATION OF PERFORMANCE**

Promenade Classicstone, Calibrated Flagstone 3m x 3m Circle Kit

**1. Product Type:** Quartzitic Sandstone**2 Unique Identification Code(s):** NPPPRCSK3-DSK**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Commercial And Domestic Paving For External Use

**4. Manufacturer:** Natural Paving Products (UK) Ltd (Stone Exporters (India) Pvt Ltd.)  
Bhudpura  
India**5. Authorised Representative:** Steve Milburn**6. System of System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:** Level 4**7. Harmonised Standard:** EN1341:2012**8. Notified Body:** N/A**9. Declared Performance**

<b>Essential Characteristic</b>	<b>Performance</b>	<b>Harmonised Technical Specification EN1341:2012</b>
Release Of Dangerous Substances	NPD	4.11
Flexural Strength - Lowest Expected Value	26.1MPa	EN12372 4.4
Slip Resistance Wet Value	51	EN14231 4.6.1
Slip Resistance Dry Value	61	EN14231 4.6.1
Skid Resistance	NPD	4.6.2
Freeze/Thaw Resistance – Mean values before and after freeze/thaw test	30.9/30.1MPa	EN12371 4.3.1
Freeze/Thaw Resistance – De-icing salts	NPD	4.3.2
Polishing In Use	NPD	4.6.3
Water Absorption	1.6%	EN13755
Abrasion Resistance	17.5mm	EN14157

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

**Name and function:** Mark Wall, Managing Director

**Place and date of issue:**

Belton Road  
Sandtoft  
Doncaster  
North Lincolnshire  
DN8 5SX

**Signature:**

A handwritten signature in black ink, appearing to read 'M. Wall', written in a cursive style.

27<sup>th</sup> April 2016